

AMENDMENTS TO THE CLAIMS

Please cancel claims 53-62 without prejudice. Please amend claims 1-4, 9-24, 30-32, and 52 as shown in the LISTING OF CLAIMS below. Claim 26 remains unchanged. Please add new claims 63-84 as shown in the LISTING OF CLAIMS. The LISTING OF CLAIMS will replace all prior versions, and listings, of claims in the present application.

LISTING OF CLAIMS

1. (Currently Amended) A backup server for enabling maintaining a call placed from a call-in user to a data communications network to recover from a local server failure, the data communications network including a local server servicing the call, and a network access server (NAS) for coupling a call placed from a call-in user the call to the data communications network local server, the NAS having a memory associated therewith, said backup server comprising:

an information packet requester responsive to the local server failure, the information packet requester requesting and receiving from the memory associated with the NAS an information packet associated with an ongoing call the call, the information packet containing call information for maintaining connection of the ongoing call to the local server; and

a parser for reconstructing the call information from the information packet, whereby such that the backup server maintains the ongoing call to the data communications network.

2. (Currently Amended) A backup server according to claim 1, wherein the call information comprises ~~includes~~ server-state attribute (SSA) having an attribute/value pair that can be parsed into a plurality of separate data entries.

3. (Currently Amended) A backup server according to claim 1, wherein the information packet further comprises ~~includes~~ a plurality of aggregated data elements from a call attribute table.

4. (Currently Amended) A backup server according to claim 3, wherein the plurality of aggregated data elements are separated by said parser for reconstructing the call information from the information packet.

5-8. (Canceled)

9. (Currently Amended) A local server for enabling ~~maintaining a call placed from a call-in user to~~ a data communications network to recover from a failure of said local sever, the data communications network including a backup server and a network access server (NAS), the NAS coupling a call placed from a call-in user to the data communications ~~the call to the~~ network, the NAS having a memory associated therewith ~~with the NAS~~, said local server comprising:

an encoder for generating an information packet associated with an ongoing ~~the~~ call, the information packet containing call information for maintaining connection of the ongoing call ~~[[to]]~~ if the local server fails; and

a sender for transmitting the information packet from the encoder to the memory associated with the NAS, the information packet being stored in the memory to be available to the backup server if the local server fails.

10. (Currently Amended) A local server according to claim 9, wherein the call information comprises ~~includes~~ server-state attribute (SSA) having an attribute/value pair that can be parsed into a plurality of separate data entries.

11. (Currently Amended) A local server according to claim 9, wherein the information packet further comprises ~~includes~~ a plurality of aggregated data elements from a call attribute table.

12. (Currently Amended) A local server according to claim 11, wherein the plurality of aggregated data elements are separated by said parser for reconstructing the call information from the information packet.

13. (Currently Amended) A system for maintaining a call placed by a call-in user to a data communications network, the network including a network access server (NAS) for coupling the call to the network, a local server servicing the call, a backup server, and a failure detector for detecting a failure of the local server, the system comprising:

a memory associated to the NAS;

an encoder associated with the local server for generating an information packet, wherein the information packet containing call information for maintaining connection of the call to the local server;

a sender for transmitting the information packet from said encoder to said memory associated with the NAS, the information packet being stored in said memory;

a call coupler associated with the NAS for coupling the call to the local server if the local server does not fail, and for coupling the call to the backup server if the local server fails;

an information packet forwarder for transmitting the information packet from said associated memory to the backup server if the local server fails; and

B
C'
a parser associated with the backup server for reconstructing the call information from the information packet ~~the call information, whereby~~ such that the backup server can recover the call information [[data]] and serve the call without disconnecting the user from the network.

14. (Currently Amended) A system according to claim 13, wherein said information packet forwarder comprises ~~includes~~:

an information packet requester associated with the backup server for requesting the information packet from said memory associated with the NAS in response to the call received from the NAS.

15. (Currently Amended) A system according to claim 14, wherein said information packet requester requests the information packet from said memory if the call information is not available to the backup server.

16. (Currently Amended) A system according to claim 14, wherein said information packet forwarder further comprises ~~includes~~:

an information packet sender associated with the NAS, for transmitting the information packet in response to a request from said information packet requester.

17. (Currently Amended) A network access server (NAS) for maintaining a call placed from a call-in user to a data communications network, the data communications network including a local server for servicing the call, and a backup server capable of servicing the call, said NAS comprising:

an receiver for receiving an information packet from the local server, the information packet containing context data of an ongoing call information for maintaining connection of the call ~~to the local server~~

an associated memory for storing the information packet;

a failure detector for determining if a failure of the local server has occurred;

~~a call coupler for coupling the call to the local server if the local server does not fail, and for coupling the call to the backup server in response to the failure of the local server; and~~

a sender for transmitting the information packet from the associated memory to the backup server if the local server failure has occurred.

18. (Currently Amended) A NAS according to claim 17, wherein the call information comprises ~~includes~~ server-state attribute (SSA) data having an attribute/value pair that can be parsed into a plurality of separate data entries.

19. (Currently Amended) A NAS according to claim 17, wherein the information packet further comprises ~~includes~~ a plurality of aggregated data elements from a call attribute table.

20. (Currently Amended) A server backup system for maintaining an ongoing call placed by a call-in user to a network, the network including a server servicing the call, a network access server (NAS) coupling the call from the user to the server, and a memory associated with the NAS, said system comprising:

a backup server connected to the network, said backup server being capable of servicing the call;

an encoder associated with the server, said encoder generating an information packet containing call information for maintaining connection of the call ~~to the local server;~~

a sender associated with the server, said sender transmitting the information packet to the memory associated with the NAS, the memory storing the information packet;

a call coupler associated with the NAS, said call coupler rolling over the call to said backup server if the server fails;

an information packet requester associated with said backup server, for requesting the information packet from the memory associated with the NAS in response to the call received from the NAS, if the call information is not available to the backup server; and

a parser associated with said backup server, for reconstructing the call information from the information packet.

21. (Currently Amended) A server backup system according to claim 20, wherein the call information comprises ~~includes~~ server-state attribute data having an attribute/value pair that can be parsed into a plurality of separate data entries.

22. (Currently Amended) A server backup system according to claim 20, wherein the information packet further comprises ~~includes~~ a plurality of aggregated data elements from a call attribute table.

23. (Currently Amended) A server backup system according to claim 22, wherein the plurality of aggregated data elements of the information packet are separated by said parser for reconstructing the call information from said information packet.

24. (Currently Amended) A server backup system according to claim 20, wherein the server is a resource pool manager server (RPMS).

25. (Canceled)

26. (Previously Amended) A server backup system according to claim 20, further comprising:

a failure detector associated with the NAS, for detecting the failure of the server.

27-29. (Canceled)

30. (Currently Amended) A server backup system for maintaining an ongoing call placed by a call-in user to a network, the network and a failure detector connected to the network for determining whether said server access failure has occurred, said memory and said failure detector both associated with a network access server (NAS) that is connected to said network, said said system comprising:

a first server connected to the network for servicing the call;

a second server connected to the network for servicing the call if the first server fails; and

a network access server (NAS) for coupling the call from the user to said first server, and coupling the call to said second server if the first server fails, said NAS including a memory associated therewith,

wherein said first server comprising including:

an encoder for generating an information packet, the information packet containing call information for maintaining connection of the call ~~to the first server~~; and

a sender for transmitting the information packet from said encoder to the memory associated with the NAS, the memory storing the information packet, and wherein said second server comprising including:

an information packet requester for requesting the information packet from the memory in response to the call received from the NAS, if the call information is not available to the second server; and

a parser for reconstructing the call information from the ~~[[said]]~~ information packet.

31. (Currently Amended) A server backup system according to claim 30, wherein said NAS further comprises ~~includes~~:

a failure detector for detecting the failure of said second server.

32. (Currently Amended) A server backup system according to claim 30, wherein said first server is a resource pool manager server (RPMS) and said second server is a backup RPMS.

33-51. (Canceled)

52. (Currently Amended) A NAS according to claim 17, wherein said sender transmits the information packet in response to a request from the backup server.

53-62. (Canceled)

63. (New) A method performed by a backup server for enabling a data communications network to recover from a local server failure, the data communications network including a network access server (NAS) for coupling a call placed from a call-in user to the data communications network, the NAS having a memory associated therewith, said method comprising:

receiving an information packet from the memory associated with the NAS in response to the local server failure, the information packet being associated with an ongoing call, the information packet containing call information for maintaining connection of the ongoing call; and

reconstructing the call information from the information packet so as to maintain the ongoing call to the data communications network.

64. (New) A method according to claim 63, wherein the call information comprises server-state attribute (SSA) data having an attribute/value pair, said reconstructing comprising:

parsing the SSA data into a plurality of separate data entries.

65. (New) A method according to claim 64, further comprising:

petitioning to the NAS for the information packet after the NAS requests the call information; and

sending the call information to the NAS after completing said reconstructing.

66. (New) A method performed by a local server for enabling a data communications network to recover from a failure of said local sever, the data communications network including a backup server and a network access server (NAS), the NAS coupling a call placed from a call-in user to the data communications network, the NAS having a memory associated therewith, said method comprising:

generating an information packet associated with an ongoing call, the information packet containing call information for maintaining connection of the ongoing call if the local server fails; and

transmitting the information packet to the memory associated with the NAS, the information packet being stored in the memory to be available to the backup server if the local server fails.

67. (New) A method according to claim 66, wherein the call information comprises server-state attribute (SSA) data having an attribute/value pair, said method further comprising:

encoding a plurality of aggregated data elements from a call attribute table representing the SSA data; and
delimiting information packet into an attribute data string and a value data string.

68. (New) A method for maintaining a call placed by a call-in user to a data communications network, the network including a network access server (NAS) for coupling the call to the network, a memory associated to the NAS, a local server servicing the call, a backup server, and a failure detector for detecting a failure of the local server, the method comprising:

generating an information packet, wherein the information packet containing call information of an ongoing call for maintaining connection of the call;

transmitting the information packet to the memory associated with the NAS, the information packet being stored in the memory;

coupling the call to the local server if the local server does not fail, and for coupling the call to the backup server if the local server fails;

transmitting the information packet from the memory associated with NAS to the backup server if the local server fails; and

reconstructing the call information from the information packet such that the backup server can recover the call context and serve the ongoing call without disconnecting the user from the network.

69. (New) A method performed by a network access server (NAS) for maintaining a call placed from a call-in user to a data communications network, the data communications network including a local server for servicing the call, and a backup server capable of servicing the call, said method comprising:

receiving an information packet from the local server, the information packet containing call information of an ongoing call for maintaining connection of the call;
storing the information packet in a memory associated with the NAS;
determining if a failure of the local server has occurred; and
transmitting the information packet from the associated memory to the backup server if the local server failure has occurred.

70. (New) A method according to claim 69, wherein the call information comprises server-state attribute (SSA) data having an attribute/value pair that can be parsed into a plurality of separate data entries.

71. (New) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform a method to be performed at a backup server for enabling a data communications network to recover from a local server failure, the data communications network including a network access server (NAS) for coupling a call placed from a call-in user to the data communications network, the NAS having a memory associated therewith, said method comprising:

receiving an information packet from the memory associated with the NAS in response to the local server failure, the information packet being associated with an

ongoing call, the information packet containing call information for maintaining connection of the ongoing call; and

reconstructing the call information from the information packet so as to maintain the ongoing call to the data communications network.

72. (New) A program storage device according to claim 71, wherein the call information comprises server-state attribute (SSA) data having an attribute/value pair, said reconstructing comprising:

parsing the SSA data into a plurality of separate data entries.

73. (New) A program storage device according to claim 72, further comprising:

petitioning to the NAS for the information packet after the NAS requests the call information; and

sending the call information to the NAS after completing said reconstructing.

74. (New) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform a method to be performed at a local server for enabling a data communications network to recover from a failure of said local sever, the data communications network including a backup server and a network access server (NAS), the NAS coupling a call placed from a call-in user to the data communications network, the NAS having a memory associated therewith, said method comprising:

generating an information packet associated with an ongoing call, the information packet containing call information for maintaining connection of the ongoing call if the local server fails; and

transmitting the information packet to the memory associated with the NAS, the information packet being stored in the memory to be available to the backup server if the local server fails.

75. (New) A program storage device according to claim 74, wherein the call information comprises server-state attribute (SSA) data having an attribute/value pair, said method further comprising:

encoding a plurality of aggregated data elements from a call attribute table representing the SSA data; and
delimiting information packet into an attribute data string and a value data string.

76. (New) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform a method to be performed at a network access server (NAS) for maintaining a call placed from a call-in user to a data communications network, the data communications network including a local server for servicing the call, and a backup server capable of servicing the call, said method comprising:

receiving an information packet from the local server, the information packet containing call information of an ongoing call for maintaining connection of the call;
storing the information packet in a memory associated with the NAS;
determining if a failure of the local server has occurred; and

transmitting the information packet from the associated memory to the backup server if the local server failure has occurred.

77. (New) A program storage device according to claim 76, wherein the call information comprises server-state attribute (SSA) data having an attribute/value pair that can be parsed into a plurality of separate data entries.

78. (New) An apparatus for enabling a data communications network to recover from a local server failure, the data communications network including a network access server (NAS) for coupling a call placed from a call-in user to the data communications network, the NAS having a memory associated therewith, said apparatus comprising:

means for receiving an information packet from the memory associated with the NAS in response to the local server failure, the information packet being associated with an ongoing call, the information packet containing call information for maintaining connection of the ongoing call; and

means for reconstructing the call information from the information packet so as to maintain the ongoing call to the data communications network.

79. (New) An apparatus according to claim 78, wherein the call information comprises server-state attribute (SSA) data having an attribute/value pair, said means for reconstructing comprising:

means for parsing the SSA data into a plurality of separate data entries.

80. (New) An apparatus according to claim 79, further comprising:
means for petitioning to the NAS for the information packet after the NAS requests the call information; and
means for sending the call information to the NAS after completing said reconstructing.

81. (New) An apparatus for enabling a data communications network to recover from a failure of said local sever, the data communications network including a backup server and a network access server (NAS), the NAS coupling a call placed from a call-in user to the data communications network, the NAS having a memory associated therewith, said apparatus comprising:

means for generating an information packet associated with an ongoing call, the information packet containing call information for maintaining connection of the ongoing call if the local server fails; and

means for transmitting the information packet to the memory associated with the NAS, the information packet being stored in the memory to be available to the backup server if the local server fails.

82. (New) An apparatus according to claim 81, wherein the call information comprises server-state attribute (SSA) data having an attribute/value pair, said apparatus further comprising:

means for encoding a plurality of aggregated data elements from a call attribute table representing the SSA data; and

means for delimiting information packet into an attribute data string and a value data string.

83. (New) An apparatus for maintaining a call placed from a call-in user to a data communications network, the data communications network including a local server for servicing the call, and a backup server capable of servicing the call, said apparatus comprising:

means for receiving an information packet from the local server, the information packet containing call information of an ongoing call for maintaining connection of the call;

means for storing the information packet in a memory associated with said apparatus;

means for determining if a failure of the local server has occurred; and

means for transmitting the information packet from the associated memory to the backup server if the local server failure has occurred.

84. (New) An apparatus according to claim 83, wherein the call information comprises server-state attribute (SSA) data having an attribute/value pair that can be parsed into a plurality of separate data entries.